

Reduced order method combined with domain decomposition method


IHP Workshop: Recent developments in numerical methods for model reduction

Davide Baroli,
Stéphane Bordas,
Lars Beex
Jack Hale

Outline

- 1 Motivation
- 2 State of Art
- 3 Linear elasticity
- 4 Domain decomposition: FETI vs Nitsche
- 5 Conclusion & Acknowledgements

- Decrease the computational cost in solving computational mechanics problem in accurate mesh discretization



Recent approach that combine reduced order modelling and spatial domain decomposition:

- Reduced basis element method based on Lagrange multiplier (FETI) method
- Static condensation reduced basis element
- Reduced basis hybrid element method
- Substructuring and heterogeneous domain decomposition method

Let $\Omega(\theta) = \Omega_1(\theta_1) \cup \Omega_2(\theta_2)$ and $\Gamma(\theta) = \partial\Omega_1(\theta_1) \cap \partial\Omega_2(\theta_2)$ the interface between the subdomains. The linear elasticity problem reads: find the displacement \mathbf{u} such that





$$\begin{aligned} -\operatorname{div}(\sigma(\mathbf{u}, \mu_i, \lambda_i)) &= f_i(\beta, \rho) && \text{in } \Omega_i(\theta_i) \\ \sigma(\mathbf{u}, \mu_1, \lambda_1) \cdot \mathbf{n} &= \sigma(\mathbf{u}, \mu_2, \lambda_2) \cdot \mathbf{n} && \text{on } \Gamma(\theta) \\ \mathbf{u}_1 &= \mathbf{u}_2 && \text{on } \Gamma(\theta) \\ \mathbf{u} &= 0 && \text{on } \partial\Omega_{D,i}(\theta_i) \\ \sigma(\mathbf{u}, \mu_i, \lambda_i) \cdot \mathbf{n} &= \mathbf{g} && \text{on } \partial\Omega_{N,i}(\theta_i) \end{aligned}$$

Here the stress tensor σ is related to the displacement by Hooke's law:

$$\sigma(\mathbf{u}_i) = 2\mu_i \epsilon(\mathbf{u}_i) + \lambda_i \operatorname{tr}(\epsilon(\mathbf{u}_i)) \mathbf{I} \quad \text{in } \Omega_i(\theta_i)$$

And source is defined as : $f_i(\beta, \rho) = (0.0, -\rho \cdot 9.8 \cdot e^{-c((x-\beta_x)^2 + (y-\beta_y)^2)})$

Reference configuration



Error estimation of RB-Greedy




Figure: Reduced basis error with parametric manifold defined by the variation of the shape and position of the source

The algebraic system reads

$$\begin{bmatrix} A_1 & 0 & B_1^T \\ 0 & A_2 & B_2^T \\ B_1 & B_2 & 0 \end{bmatrix} \begin{bmatrix} u_1 \\ u_2 \\ \lambda \end{bmatrix} = \begin{bmatrix} f_1 \\ f_2 \\ 0 \end{bmatrix} \quad (1)$$

where B_i are signed boolean matrices. Cons:

- additional effort for each floating block and corner point
- mortar integration or interpolation for non-matching case

In no-floating case, the reduced FETI system could be rewritten in the following way:

$$(B_1^T Z_1 (A_1^r)^{-1} Z_1^T B_1 + B_2^T Z_2 (A_2^r)^{-1} Z_2^T B_2) \lambda = 0$$

$$A_1^r u_1^r + Z_1^T B_1 \lambda = Z_1^T f_1$$

$$A_2^r u_2^r + Z_2^T B_2 \lambda = Z_2^T f_2$$

where Z_i matrix contains the reduced basis (column-wise)

Find $u \in H^1(\Omega)$ such that


$$\sum_i \int_{\Omega_i} \sigma(\mathbf{u}) : \nabla v - \int_{\Gamma} \langle \sigma(\mathbf{u}) \cdot \mathbf{n} \rangle \llbracket v \rrbracket \\ - \int_{\Gamma} \langle \sigma(\mathbf{v}) \cdot \mathbf{n} \rangle \llbracket u \rrbracket + \frac{\alpha}{h} \int_{\Gamma} \llbracket u \rrbracket \llbracket v \rrbracket = \sum_i \int_i f_i v \quad \forall v \in H_0^1(\Omega)$$

The implementation in FeNicS is based on recent “Multimesh, MultiMeshFunctionSpace” .

Using an parametrization, the Nitsche formulation on the reference block could be written as



$$\begin{aligned} & \sum_i \int_{\Omega_i} G(\mu) \cdot \sigma(\mathbf{u},) : G(\mu) \cdot \nabla v \det(G^{-1}(\mu)) dV_i \\ & - \int_{\Gamma} \langle \sigma(\mathbf{u}) \cdot \mathbf{n} \rangle \llbracket v \rrbracket \| G(\mu) \cdot \mathbf{e}_t \| dl \\ & - \int_{\Gamma} \langle \sigma(\mathbf{v}) \cdot \mathbf{n} \rangle \llbracket u \rrbracket \| G(\mu) \cdot \mathbf{e}_t \| dl \\ & + \frac{\alpha}{h} \int_{\Gamma} \llbracket u \rrbracket \llbracket v \rrbracket \| G(\mu) \cdot \mathbf{e}_t \| dl = \sum_i \int_i f_i v \quad \forall v \in H^1(\Omega) \end{aligned}$$

Test case I





RUE


Reduced basis pairs: (1,5), (2,5)




Reduced basis pairs: (3,5), (4,5)




Reduced basis pairs: (5,5)




Test case II: Non-matching







u_Y



Number of Reduced Basis:1-4 and 2-4



Number of Reduced Basis:3-4 and 4-4



The preliminar numerical comparison evidences:

- more flexible approach in online gluing with Nitsche formulation
- combination of reduced basis provides a speed in solving the system

Working in progress:

- investigation on different reference lego block configuration
- integration of EIM tool
- extension to realistic configuration in biomechanics problem
- real-time cut-tracking
- release of a python module based on FeNicS, petsc4py and slepc4py for reduced order method approaches.



European Research Council

Established by the European Commission

European Research Council Starting Independent Research Grant (ERC Stg grant agreement No. 279578) entitled "Towards real time multiscale simulation of cutting in non-linear materials with applications to surgical simulation and computer guided surgery" led by Stéphane P. A. Bordas

Thank you for your attention

